



Specifications Philips LED SlimDownlight Coreline DN145C 21W 2100lm 84D - 830 Warm White | 222mm - IP44

[View Product](#)

General Information

| | |
|--------------------------|-----------------------------|
| SKU | 235941 |
| EAN | 8710163339535 |
| manufacturer_code | 33953599 |
| Brand | Philips |
| Manufacturer Name | DN145C LED20S/830 PSU II WH |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 35000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Wattage | 21W |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light Colour Options | Single Color |

| | |
|-----------------------|--------------------------------|
| Driver Included | Yes |
| Beam Angle (degree) | 84 |
| Luminous Flux (Lumen) | 2100lm |
| Lumen per watt | 100 |
| Power factor | >0.90 |
| Unified Glare Rating | < 28 |
| Optical Cover | PMMA (Polymethyl methacrylate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------|
| EOC8 | 33953599 |
| Mounting Method | Surface |
| Cut out (mm) | 222 |
| IP-Rating | IP44 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature | 0 to +35 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | Cable, 2-pole |
| Series | DN145C |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 50 |
| Diameter (mm) | 222 |

Sensor Information

Type of sensor

No Sensor

Why Any-lamp?



Order from the **largest lighting specialist** in Europe



Customised quotation



Up to **7 years warranty**



Easy return process

