



Specifications Noxion LED Panel Delta Pro V5 28W 3700lm - 830 Warm White | 60x60cm - UGR <19 - Sidelit - Philips Driver

[View Product](#)

General Information

| | |
|--------------------------|--|
| SKU | 257876 |
| EAN | 8719157073868 |
| manufacturer_code | 8719157073868 |
| Brand | Noxion |
| Manufacturer Name | Noxion LED Panel Delta Pro V5.1 28W 3700lm 3000K 600*600 (Philips Driver) UGR<19 Sidelit NDL |
| Any Lamp all-in warranty | 6 Years |
| Average Lifetime (h) | 100000 |
| Series | Delta Pro |

Technical Information

| | |
|-----------------------------|-----------------|
| Technology | LED Integrated |
| Replaces (Watt) | 4x18 |
| Wattage | 28W |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light Colour Options | Single Color |

| | |
|------------------------|-------------------|
| Luminous Flux (Lumen) | 3700lm |
| Lumen per watt | 132 |
| IP-Rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection | Push Terminal |
| Finish of Reflector | Frosted |
| Power factor | >0.90 |
| Product Type Category | LED Panel |

Fixture Information

| | |
|-----------------------|-------------------|
| Mounting Method | Recessed |
| Unified Glare Rating | < 19 |
| Optical Cover | PS (Polystyrene) |
| Operating Temperature | -20 to +40 |
| Emergency Lighting | No Emergency Unit |
| Colour of the Fixture | White |
| Housing | Steel |

Dimensions

| | |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm) | 595 |
| Width (mm) | 595 |
| Height (mm) | 10 |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



Easy return process